

400 SERIES BASES



400-3



415



425



440



460

400 SERIES

- Corner mount legs
- Constructed of 14 gauge tubular steel
- Top mounting plate is welded to leg, with all corners and edges radiused to eliminate sharpness
- C/w adjustable glides, 1 $\frac{5}{8}$ " dia nylon pad, $\frac{5}{16}$ " x 1 $\frac{1}{4}$ " threaded stem
- **#400-2:** 2" dia leg with 5" x 5" x $\frac{3}{16}$ " thick mounting plate
- **#400-2.5:** 2 $\frac{1}{2}$ " dia leg with 7" x 7" x $\frac{3}{16}$ " thick mounting plate
- **#400-3:** 3" dia leg with 10" x 10" x $\frac{3}{16}$ " thick triangular mounting plate
- **#400-4:** 4" dia leg with 12" x 12" x $\frac{3}{16}$ " thick mounting plate
- **#400-6:** 6" dia leg with 12" x 12" x $\frac{3}{16}$ " thick mounting plate

415 SERIES

- Corner mount legs
- Legs are oval shaped, 1 $\frac{1}{2}$ " x 3 $\frac{1}{4}$ "
- Constructed of 14 gauge tubular steel
- Top mounting plate is $\frac{3}{16}$ " thick, triangular shaped, welded to leg, with all corners and edges radiused to eliminate sharpness
- C/w adjustable glides, 1 $\frac{5}{8}$ " dia nylon pad, $\frac{5}{16}$ " x 1 $\frac{1}{4}$ " threaded stem

425 SERIES

- Corner mount legs
- Legs are triangular shaped, 2 $\frac{3}{8}$ " x 3 $\frac{1}{2}$ " aluminum extrusion
- C/w two channels for securing vertical wire manager compartment
- Top mounting plate is $\frac{3}{16}$ " thick, triangular shaped, with all corners and edges radiused to eliminate sharpness, secured to leg with three bolts
- C/w adjustable glides, 1 $\frac{5}{8}$ " dia nylon pad, $\frac{5}{16}$ " x 1 $\frac{1}{4}$ " threaded stem

BASE SPECIFICATIONS

440 SERIES

- Corner mount legs
- Legs are 3" dia, tapered to 1 $\frac{1}{2}$ "
- Constructed of 14 gauge tubular steel
- Top mounting plate is 8" x 8" x $\frac{3}{16}$ " thick, double bolted to 3" dia leg opening
- Includes a choice of 1 $\frac{1}{2}$ " dia adjustable glide or 2" dia twin wheel locking caster

460 SERIES

- Corner mount legs
- Legs are racetrack shape, 2" x 4 $\frac{1}{4}$ " aluminum extrusion
- C/w two channels for securing vertical wire manager compartment
- Top mounting plate is $\frac{3}{16}$ " thick, triangular shaped, with all edges and corners radiused, secured to leg with four bolts
- C/w adjustable glides, 1 $\frac{5}{8}$ " dia nylon pad, $\frac{5}{16}$ " x 1 $\frac{1}{4}$ " threaded stem

OPTIONAL

- Equalizer glides
- Casters for mobility

TUFF-EDGE INC.

108 Carnforth Road
North York, Ontario
M4A 2L4

T. 416.757.8201
F. 416.757.4438
Toll Free. 1.877.846.5854
sales@tuff-edge.com

www.**TUFF-EDGE**.com

Printed in Canada

DP 33794

400 SERIES BASES



400-3



400-3



440



440



415



415



425



425



460



460